

ILS Synergy IM Presenter lectern

Designed for upscale boardrooms, showrooms and prestigious events, the new **Synergy IM** uses the same proven multi-touch glass technology as our previous ILS22 generation.

This seamless sheet of 5 mm safety glass offers 10 point multi-touch with an integrated 29" ultrawide 2560x1080 display, a 12" control panel, a trackpad and a multifunctional keyboard with changing key layouts.

The keyboard is fully customizable, our ILS Control Software can display virtually any keyboard layout.





Dimensions

Width	No side plates: 42cm pillar, 70cm top With side plates: 156cm top side plate size: 36cm x 26cm
Height	User side min: 94cm, max: 120cm Audience side min: 114cm, max: 140cm casters add 7cm
Weight	70kg

Integration

Computer support	29" 21:9 IPS Display 12" Touch Keyboard and Control Panel Configurable industrial Mini-ITX motherboard with latest Intel® Core™ processor
Audio	1 x shock mount XLR socket 1 x regular mount XLR-3 pin Socket for microphone (or 1 x regular mount XLR-4 pin for the reading light) Optional 4 speakers integrated into the top with 280W amplifier.

Connectivity

Side connectivity panel	Laptop connectivity: HDMI, DP, VGA and 3.5 Audio, Ethernet Integrated computer expansion ports: 2 x USB Sockets for external USB devices	
Top dashboard	8" wide tablet holder for control panels and tablets with integrated Apple Lightning and/or Micro USB charging plugs 	Integrated computer expansion ports: 2 x USB Sockets for external USB devices
Bottom cabling	Second display connection HDMI of integrated computer HDMI, DP, VGA and 3.5 Audio cables from connectivity side panel or integrated 4x1 HDMI switcher with only one HDMI/CAT6 cable in the bottom. Ethernet, Power, Microphone output: XLR cable per microphone	