

ILS Synergy HT

ILS Synergy HT keeps the handrails exposed, where the WW-model optimizes the width of the wood. Custom integration of tablets is also possible with this system.

The preferred option for this lectern is the Audio Upgrade which will add a speaker array in the front, making the lectern a fully self-supporting speaking system for rooms up to 100 people.

There is also ample room inside the lectern to house additional control systems by creating space inside the wooden surface.





Dimensions

Width	No side plates: 20cm pillar, 70cm top With side plates: 140cm top side plate size: 36cm x 26cm
Height	User side min: 80cm, max: 120cm Audience side min: 94cm, max: 134cm
Weight	60kg

Integration

Computer support	Place you laptop on top surface or sideplates. Wooden top surface Size: 50 x 45 Handrails opened
Audio	1 x shock mount XLR socket 1 x regular mount XLR-3 pin Socket for microphone (or 1 x regular mount XLR-4 pin for the reading light) Optional 4 speakers integrated into the top with 280W amplifier.

Connectivity

Side connectivity panel	Laptop connectivity: HDMI, DP, VGA and 3.5 Audio, Ethernet 2 x USB Sockets for external USB devices (There is no internal PC, customer decides how to use these ports)	
Top dashboard	8" wide tablet holder for control panels and tablets with integrated Apple Lightning and/or Micro USB charging plugs	 Integrated computer expansion ports: 2 x USB Sockets for external USB devices
Bottom cabling	HDMI, DP, VGA and 3.5 Audio cables from connectivity side panel or integrated 4x1 HDMI switcher with only one HDMI/CAT6 cable in the bottom. Ethernet, Power, Microphone output: XLR cable per microphone	