

ILS prides itself to build the highest quality lecterns around from thick aluminum profiles, blocks and plates, machined to a perfect fit and style. The lecterns are virtually free of maintenance for decades. In ILS products it is possible to remove a damaged part and renew it, or to make new fittings for future upgrades without affecting the rest of the installed system.

ILS Synergy QW delivers ILS quality with a smart design. The solid top of the lectern is placed on a motorized wide pillar with a height adjustment range up to 40 cm (15 "+). Two buttons will help you to control it.

Long version of the top is divided into two working areas. On the left is a monitor 24", mounted inside the working surface. On the right is a smooth aluminum surface for handwritten notes, laptop or installed control panel. A holder for the micro PC is installed inside the working surface. This lectern also provides one sliding horizontal side table (or two fixed side tables) moving up or down with the top. This makes it possible to use extra space for handwritten notes, laptop, or place a document camera on it. The built-in switcher or four sockets with the type on request will be great helpers when handling connections between the main screen of the lectern and/or laptop, or other devices. To do this, there are four buttons on the top panel of the product. There are also AC power socket and two USB 3.0 sockets and a holder with built-in charging cables for tablets and smartphones. The microphone socket is of the XLR shock-mount type and there is the provision for a reading light, controlled by the button. Additionally, for greater convenience, a keyboard tray can be integrated.

For ease of movement and stability of the lectern during the presentation, four lockable smart castors are provided. In addition, we will be pleased to engrave your logo on the front panel of the lectern, in case of using the system in formal events!



DIMENSIONS

Width	Top: 1030 mm x 545 mm Side Plate: 430 mm x 295 mm Top + Side Plate: 1430 mm
Height	User side: min: 950 mm max: 1355 mm Audience Side: min: 1075 mm max: 1480 mm
Weight	85 kg

INTEGRATION

Display & PC	Monitor: 24" Dell 2418HT IPS; 10 points capacitive touchscreen (Up to 30") PC: Dell Optiplex 3070 micro Intel Core I-5 CPU; 8GB RAM; 256GB SSD;
Accessories	Switcher: ILS503 or 4 x sockets (type on request) Audio: 1 x Microphone AKG CGN 99 Light: 1 x LITTLITE LED BNC lamp
Features	ILS holder for micro PC installation inside working surface Extra space on the right from the display for laptop or notes <27" monitor Ultra Wide Phone/Tablet holder Height adjustment: Motorised Wide Pillar 40cm range height 7 x Buttons (2 x Height control; 1 x Light; 4 x Signal switch;) 1 x Sliding table (right) 4 x lockable smart castors or sideways rollers

CONNECTIVITY

Top	1 x 3-Pin XLR Shock Mount for microphone 1 x BNC Light socket (12V) 2 x USB 3.0 Sockets 3 x Charging cables (USB type-C; Lightning; micro USB;) 1 x AC Power socket
Bottom	1 x HDMI; 1 x PC LAN; 1 x XLR microphone; 1 x 3.5mm Audio; 1 x AC Power; 1 x HDbaseT; 1 x Switcher Control Cable;