

## 2 New Podium style solutions from ILS:

### ILS24HX: SpeakersCorner custom configurable lectern

- Compact podium: 26" wide, 30" deep, 41" tall, everything fits or slides into the box that is completely lockable with electromagnetic locks and accessible by IC security card.
- When closed it can serve as an audio and notebook only supported system, there is access to laptop hook-up, the microphone and a pre-cut area that can hold an AMX or Crestron control panel or Extron, Bosch etc... These sections slide out when needed. We normally recommend using the 12" touch monitor in combination with room control systems.
- Main display is on a lift and lifts from the system and tilts the display tray to the desired angle, there is no display included, and customer may install any display on its VESA mount.
- Top level: slides out flat to hold a notebook with flip-top connection panel. The top has 2 XLR3 sockets for microphones (one can be exchanged with an XLR5 socket for a switchable pre-amp microphone) and an XLR4 socket for a Littlite reading light. There are 5 buttons on the presenter side of the system to control display height, display angle, reading light, mute and auxiliary switch, e.g. use to return to the control monitor on the 12" touch monitor if it is used for other purposes as well...
- Second level: slides out in opposite direction, includes a 12" touch panel with VGA connector, this is connected to a controller system for device and room control. This display can rotate and tilt in many directions. It includes 4 USB slots on its front edge.
- Third level: Display tray with VESA mounts accommodates various display types (fits e.g. 17", 19", 22" WACOM; 17", 22" SMART Sympodium; 22" ELOtouch APR touch.)
- Fourth level down: keyboard and touch pad tray, this includes the new Bamboo pen & touch high resolution drawing pad that will now include finger touch and multitouch.
- Fifth level: large pull-out tray to hold a document camera, other laptop or otherwise serves as a table (front folds out) for seated persons to present from this level using the 12" monitor and gooseneck microphone tilted towards this direction, this makes the system ADA compliant.
- Sixth level down 19" rack area behind lockable doors with 12U rack space offers the space for any of the customer's 19" rack and PC equipment.
- A handle on top and rollers on the bottom allow for movement of the entire system.



NOTE: Specifications subject to change while product is under development

## ILS24HF Turn-key All-in-One SpeakersCorner lectern

- All of ILS24HX plus:
- 17" Lenovo SXGA display monitor pre-installed
- 1 gooseneck condenser super cardioid microphone, 1 lapel mic, 1 hand held wireless mic, microphone mixer in 19" rack
- 2x 100 watt actively ventilated, quality frequency shift amplifier, 6 mic / 2 line inputs
- A central control unit operated from the 12" touch panel with 3x2 VGA switch, 6x2 Video switch, 6x2 audio switch, 3 COM ports, MIC input, 8 IR controls; web control unit, 8 relay power control, 4 detection ports, alarm detection module, IC reader detection, all equipment is controllable over IP using the ILS room-Q software
- An optional matrix switcher allows this 12" panel to be either room control panel, confidence monitor for output to projection, control monitor for secondary (streaming studio) PC or a teleprompter surface (with optional pole and glass set ordered)
- Webcam on USB on top
- Room-Q remote control client and sho-Q presenter delivery software

### Options:

(user-selectable components shipped separately along with the ILS24H, to be priced and detail specs to follow)

- Rack PC, pre-configured
- 4x4 VGA + audio switcher with serial control
- WACOM pen display 17 – 19 – 22" versions included with shipment
- PTZ camera for streaming applications or surveillance
- Document camera
- Room-Q server system: remote assistance and control, banner messages to all rooms, streaming to multiple rooms, recording, surveillance, maintenance scheduling
- Customized front panel, material choice and color choice with engraved logo options
- Teleprompter kit, pole and glass set, sho-Q extension
- Alarm system (110+ dB), signal to control room



(Availability 2010 Q1; click [www.intelligentlecterns.com/support/pictures/ils24/ils24h.html](http://www.intelligentlecterns.com/support/pictures/ils24/ils24h.html) for the latest design status)  
For more details contact Henk de Groot at +31 20 2400 232 or email to [henk.degroot@intelligentlecterns.com](mailto:henk.degroot@intelligentlecterns.com)

NOTE: Specifications and pricing subject to change while product is under development